



UNILOCK PAVERS

JOINT SAND

3/8 INCH AGGREGATE CHIP SETTING BED; CRUSHED, ANGULAR

1/8 INCH THICK BY 4 INCH WIDE GALVANIZED STEEL ANGLE IRON

STAINLESS STEEL ANCHOR BOLT; 12" O.C. (TYP.)

3/4 INCH BY 12 INCH LONG DOWELS @ 12" O.C. (TYP.)

1-1/2 INCH WEEP HOLE, 12 INCHES O.C.; FILL WITH 3/8 INCH CHIP

6X6 INCH W.W.M., 2 INCH CLEAR (TYP.)

#4 REBAR, 9 INCHES O.C.; CONTINUOUS

CONCRETE CURB

GRANULAR BASE

COMMERCIAL APPLICATION PAVER DETAIL (CONCEPTUAL)

CREATED: AUGUST 29, 2013

REVISED: MARCH 6, 2014

FILE NAME: CS-11-COM-PAVER-CONC-UNDER.DWG

NOTES:

This cross section is intended for CONCEPTUAL DESIGN purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

CROSS SECTION

PAVERS ON CHIP WITH CONCRETE UNDERLAYMENT, STEEL EDGE

UNILOCK
DESIGNED TO CONNECT.

