

Safety Data Sheet

BP Pro

2941 W. MacArthur Blvd, Suite 138
Santa Ana, CA 92704



24 Hour Emergency:

Infotrac: 1-800-535-5053

Outside U.S And Canada

Infotract: 352-323-3500

Note: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

SECTION 1 – CHEMICAL PRODUCT/ COMPANY INFORMATION

Product Name: WetLOOK Solvent Based Sealer

Manufacturer: S Vann Inc., DBA BP Pro
2941 W MacArthur Blvd, Suite 138
Santa Ana, CA 92704

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May be fatal if swallowed. Suspect cancer hazard. Extremely flammable liquid and vapor.

GHS Classification

Carc. 2, Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE, Skin irrit. 2

Symbols of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Carcinogenicity, category 2	H351	Suspected of causing cancer.
Eye irritation, category 2	H319	Causes serious eye irritation.
Flammable liquid, category 2	H225	Highly flammable liquid and vapor.
STOT, single exposure category 3, NE	H336	May cause drowsiness or dizziness.
	H315	Causes skin irritation.

GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat and hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313

If exposed or concerned: Get medical advice/attention.

P312

Call a POISON CENTER/doctor/physician if you feel unwell.

P321

Specific treatment (see first aid section on this label).

P332+P313

If skin irritation occurs: Get medical advice/attention.

P337+P313

If eye irritation persists: Get medical advice/attention.

P362 + P364

Take off contaminated clothing and wash it before reuse.

P370 + P378

In case of fire: Use appropriate method to extinguish.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
2-propanone	67-64-1	50-75	GHS02-GHS07	H225-319-336
Xylene	1330-20-7	2.5-10	GHS02-GHS07-GHS08	H226-315-319-332-335-351-373
Ethylbenzene	100-41-4	1.0-2.5	GHS02-GHS07-GHS08	H225-315-319-332-335-373

The text for GHS Hazard Statements shown above (if any) is given in the “Other information” section.

SECTION 4 – FIRST AID MEASURES



FIRST AID – EYE CONTACT: Remove contact lenses if worn. Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

FIRST AID – SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.

FIRST AID – INHALATION: Rescuers should put on appropriate gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID – INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

UNUSUAL FIRE AND EXPLODING HAZARDS: Extremely flammable liquid and vapor. Vapors/dust may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Avoid use of solid water streams. Do not use water jet (frothing possible). Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition.

EXTINGUISHING MEDIA: Carbon dioxide, Dry Chemical, Foam, Water Fog

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert materials (e.g dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Use only non-combustible material for clean up. Remove from surface by skimming or with suitable absorbents. Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Collect spilled materials for disposal. Wear appropriate personal protective equipment. (See exposure controls/Personal Protection Section.) A vapor suppressing foam may be used to reduce vapors.

SECTION 7 – HANDLING AND STORAGE



HANDLING: Use only in a well ventilated area. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues. Avoid contact with eyes, skin, and clothing. Always open containers slowly to allow any excess pressure to vent. When transferring, follow proper grounding procedures. Use spark-resistant tools. Avoid breathing vapor, fumes or mist. Use explosion proof equipment. Take precautionary measures against static discharge.

STORAGE: Containers can build up pressure if exposed to heat (fire). Keep away from heat, sparks, and flame. Keep container closed when not in use. Protect from direct sunlight. Store containers in a cool, well-ventilated place. Material is a static accumulator, which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
2-propanone	500 ppm	750 ppm	1000 ppm	N.D
Xylene	100 ppm	150 ppm	100 ppm	N.D
Ethylbenzene	100 ppm	125 ppm	100 ppm	N.D

Personal Protection



Respiratory protection: A NIOSH/MSHA approved respirators may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.



Skin Protection: Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed – apron, suit, boots. Wear long sleeves when contact is likely to occur.



Eye Protection: Wear safety glasses with side shields (or goggles) and a face shield.



Other Protective equipment: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



Hygienic practices: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and wash before reuse. Avoid breathing vapors. Do not eat, drink, or smoke in areas where this material is used.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid	Physical State:	Liquid
Odor:	Typical	Odor Threshold:	N.D
Density, g/cm3:	.852	pH:	N.D
Freeze Point, F:	N.D	Viscosity:	N.D
Solubility in water:	Partial	Explosive Limits, vol%:	1.0 – 12.8
Boiling Range, F:	133-288	Flash Point, F:	0
Evaporation Rate:	N.D	Auto Ignition Temp., F:	N.D
Vapor Density:	N.D	Vapor Pressure:	N.D

SECTION 10 – STABILITY AND REACTIVITY

Stability: No information

Conditions to avoid: Avoid impact, friction, heat, sparks, flame and source of ignition.

Incompatibility: Keep away from acids. Prevent contact with strong oxidizing agents. Keep separate from alkalies. Prevent contact with halogens.

Hazardous Decomposition products: Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon dioxide may be formed. During combustion carbon monoxide may be formed. Decomposition releases nitrogen oxides.

Hazardous Polymerization: N.D.

SECTION 11 – TOXICOLOGICAL INFORMATION



Information on Toxicological Events

Effects of Overexposure – Inhalation: Breathing saturated vapors for a few minutes may be fatal. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation. Prolonged inhalation may be harmful. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Breathing in material may irritate the mucous membranes of the nose, throat bronchi and lungs. May cause dizziness or drowsiness.

Effects of Overexposure – Skin Contact: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product. Can be absorbed through skin and produce central nervous system effects. Contact with skin may cause mild irritation.

Effects of Overexposure – Eye Contact: Causes eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Effects of Overexposure – Ingestion: May be fatal if swallowed. Ingestion may result in nausea, vomiting, diarrhea, and restlessness. May cause dizziness and drowsiness or stupor. Ingestion may cause gastrointestinal tract irritation. May cause nausea and diarrhea. Aspiration hazard if swallowed – can enter lungs and cause damage.

Effects of Overexposure – Chronic Hazards: Suspect cancer hazard. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes. Possible brain damage from overexposure. The international Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

Primary Routes of Entry: Skin contact, skin absorption, inhalation, eye contact

Acute Toxicity Values

The Acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50,mg/L</u>
67-64-1	2-propanone	>2900.0	>2000.0	N.D
1330-20-7	Xylene	>3523	>4200	>20.0
100-41-4	Ethylbenzene	3500	15433	>20.0

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information.

SECTION 13 – DISPOSAL CONSIDERATIONS



For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always Dispose of any waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert materials (e.g dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Use only non-combustible material for clean up. Remove from surface by skimming or with suitable absorbents. Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Collect spilled materials for disposal. Wear appropriate personal protective equipment. (See exposure controls/Personal Protection Section.) A vapor suppressing foam may be used to reduce vapors.

SECTION 14 – TRANSPORT INFORMATION

DOT Proper Shipping
DOT Hazard Class:
DOT UN/NA Number:

Paint related material
3
UN1263

Packing Group:
Hazard Subclass:
Resp. Guide Page:

II
No information
128

SECTION 15 – REGULATORY INFORMATION

U.S Federal Regulations:

CERCLA – SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA Section 313:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylene	1330-20-7
Ethylbenzene	100-41-4
Methanol	67-56-1

Toxic Substance Control Act:

All components of this product are listed or exempt from listing on the TSCA 8(b) inventory. If identified components of this product are listed under the TSCA 12(b) export notification rule, they will be listed below.

No TSCA components exist in this product.

US State Regulations:

New Jersey Right-To-Know:

The following materials are non-hazardous but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
Poly (methyl methacrylate/n-butyl metacrylate/methacrylic acid	28262-63-7

Pennsylvania Right to Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
Poly (methyl methacrylate/n-butyl metacrylate/methacrylic acid	28262-63-7

California Proposition 65 Carcinogens

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylbenzene	100-41-4

California Propositions 65 Reproductive Toxins

Warning: The following ingredients present in the product are known to the state of California to cause birth defects or other reproductive hazards:

<u>Chemical Name</u>	<u>CAS-No.</u>
Methanol	67-56-1

International Regulations: As follows -

Canadian WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No information.

SECTION 16 - OTHER INFORMATION

Revision Date: 6/16/2015 Supersedes Date: New SDS
 Datasheet produced by: EH&S

HMIS Ratings:

Health:	1	Flammability:	3	Reactivity:	0 – No hazard	Personal Protection:	N.I
----------------	---	----------------------	---	--------------------	---------------	-----------------------------	-----

Volatile Organic Compounds, gr/ltr: 99

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, BP PRO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapor.
 H226 Flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS07



GHS08



Legend: N.A – Not Applicable, N.E – Not Established, N.D – Not Determined, N.I – No Information.

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of in any way connected with handling, storage, use, or disposal of this product. IF the product is used as a component of another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local Laws and regulations.