



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product name : Gator Clean RPT Remover +
Product code : N/A
Other means of identification : Emulsified solvent.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coatings: Cleaner
Supplier : Alliance Designer Products Inc.
225 Blvd Bellerose West
Laval, Quebec
Canada
H7L 6A1
www.alliancegator.com

24 hour Emergency Phone : Canada : 1-613-996-6666 (Canutec)
United States : 1-800-424-9300 (Chemtrec)

SECTION 2 - HAZARDS IDENTIFICATION

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 4
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

GHS label elements : Hazard pictograms



Signal word : Danger
Hazard statements : Flammable liquid and vapor.
Harmful if swallowed or in contact with skin.
Causes serious eye irritation.
Causes skin irritation.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture

Ingredient name	%	CAS number
xylene	≥52 - <75	1330-20-7
Butyl Cellosolve	≥4 - <5	111-76-2
Isopropyl alcohol	≥3 - <4	67-63-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4 - FIRST AID MEASURES

DESCRIPTION OF NECESSARY FIRST AID MEASURES

- Eye contact :** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation :** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact :** Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion :** Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 4 - FIRST AID MEASURES (CONT.)

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

POTENTIAL ACUTE HEALTH EFFECTS

Eye contact : Causes serious eye irritation.
Inhalation : May cause respiratory irritation.
Skin contact : Harmful in contact with skin. Causes skin irritation.
Ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways.

OVER-EXPOSURE SIGNS/SYMPTOMS

Eye contact: Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation: Adverse symptoms may include the following:
respiratory tract irritation
coughing

Skin contact: Adverse symptoms may include the following:
irritation
redness

Ingestion: Adverse symptoms may include the following:
nausea or vomiting

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SEE TOXICOLOGICAL INFORMATION (SECTION 11)

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 5 - FIRE FIGHTING MEASURES (CONT.)

Specific hazards arising from the chemical :

Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products :

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters :

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters :

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For non-emergency personnel :

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders :

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Small spill :

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.

Large spill :

Stop leak if without risk. Move containers from spill area. Absorb spillage to prevent material damage. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Protective measures :

Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene :

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities :

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in corrosive resistant container with a resistant inner liner. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

CONTROL PARAMETERS

Occupational exposure limits

Ingredient name	Exposure limits
xylene	<p>ACGIH TLV (United States, 4/2014). TWA: 100 ppm 8 hours. TWA: 434 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 655 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.</p>





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT.)

Butyl Cellosolve	<p>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 120 mg/m³ 8 hours.</p> <p>NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 5 ppm 10 hours. TWA: 24 mg/m³ 10 hours.</p> <p>ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours.</p> <p>OSHA PEL (United States, 2/2013). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 240 mg/m³ 8 hours.</p>
Isopropyl alcohol	<p>ACGIH TLV (United States, 4/2014). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours.</p>

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT.)

INDIVIDUAL PROTECTION MEASURES

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

SKIN PROTECTION

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Physical state : Liquid.
Colour : Colorless to light yellow.
Odour : Not available.
pH : 6.8
Melting point : -26°C (-14.8°F)
Boiling point : >132°C (>269.6°F)





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (CONT.)

Flash point :	Closed cup: 27°C (80.6°F)
Evaporation rate :	Not available.
Vapor pressure :	Not available.
Vapor density :	Not available.
Relative density :	0.8825
Solubility in water :	Not available.
Viscosity :	Not available.
VOC :	Not available.

SECTION 10 - STABILITY AND REACTIVITY

- Reactivity :** No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability :** The product is stable.
- Possibility of hazardous reactions :** Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid :** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials:** Reactive or incompatible with the following materials:
oxidizing materials
- Hazardous decomposition products :** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 - TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Butyl Cellosolve	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapor	Rat	450 ppm	4 hours
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Dermal	Rabbit	630 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LD50 Oral	Rabbit	300 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LD50 Oral	Rat	470 mg/kg	-
LDLo Oral	Human	143 mg/kg	-	
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Mouse	3600 mg/kg	-
	LD50 Oral	Rabbit	6410 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
	LD50 Oral	Rat	5045 mg/kg	-





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 11 - TOXICOLOGICAL INFORMATION (CONT.)

IRRITATION/CORROSION

Product/ingredient name	Result	Species	Score	Exposure
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams
	Skin - Mild irritant	Rat	-	8 hours 60 microliters
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams
	Skin - Moderate irritant	Rabbit	-	100 Percent
Butyl Cellosolve	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams
	Eyes - Severe irritant	Rabbit	-	100 milligrams
	Skin - Mild irritant	Rabbit	-	500 milligrams
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams
	Eyes - Moderate irritant	Rabbit	-	10 milligrams
	Eyes - Severe irritant	Rabbit	-	100 milligrams
	Skin - Mild irritant	Rabbit	-	500 milligrams

SENSITIZATION

Mutagenicity

Product/ingredient name	Experiment	Result
Not available.		

CARCINOGENICITY

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

CLASSIFICATION

Product/ingredient name	OSHA	IARC	NTP
xylene	-	3	-
Butyl Cellosolve	-	3	-
Isopropyl alcohol	-	3	-





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 11 - TOXICOLOGICAL INFORMATION (CONT.)

REPRODUCTIVE TOXICITY

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Not available.						

TERATOGENICITY

Not available.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

Not available.

Name	Category	Route of exposure	Target organs
xylene	Category 3	Not applicable.	Respiratory tract irritation
Isopropyl alcohol	Category 3	Not applicable.	Narcotic effects

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)

Name	Category	Route of exposure	Target organs
xylene	Category 2	Inhalation	ears

ASPIRATION HAZARD

Name	Result
xylene	ASPIRATION HAZARD - Category 1

POTENTIAL ACUTE HEALTH EFFECTS

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Harmful in contact with skin. Causes skin irritation.
- Ingestion** : Harmful if swallowed. May be fatal if swallowed and enters airways.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
irritation
redness





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 11 - TOXICOLOGICAL INFORMATION (CONT.)

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

**DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC
EFFECTS FROM SHORT AND LONG TERM EXPOSURE**

SHORT TERM EXPOSURE

Potential immediate effects : Not available.
Potential delayed effects : Not available.

LONG TERM EXPOSURE

Potential immediate effects : Not available.
Potential delayed effects : Not available.

POTENTIAL CHRONIC HEALTH EFFECTS

General : May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

NUMERICAL MEASURES OF TOXICITY

ACUTE TOXICITY ESTIMATES

Route	ATE value
Oral	703.4 mg/kg
Dermal	1615.6 mg/kg
Inhalation (vapors)	247.7 mg/l

SECTION 12 - ECOLOGICAL INFORMATION

TOXICITY

Product/ingredientname	Result	Species	Exposure
xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 3.3 mg/l	Fish	96 hours
	Acute LC50 8.2 mg/l	Fish	96 hours
	Acute LC50 8.6 mg/l	Fish	96 hours
	Acute LC50 12 mg/l	Fish	96 hours
	Acute LC50 13.3 mg/l	Fish	96 hours
	Acute LC50 13.4 mg/l	Fish	96 hours
	Butyl Cellosolve	Acute EC50 1000 mg/l Fresh water	Daphnia - Daphnia magna
Acute LC50 1000 mg/l Marine water		Crustaceans - Chaetogammarus marinus - Young	48 hours
Acute LC50 1490 mg/l		Fish	96 hours
Acute LC50 1250000 µg/l Marine water		Fish - Menidia beryllina	96 hours
Isopropyl alcohol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1400000 µg/l	Fish - Gambusia affinis	96 hours





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 12 - ECOLOGICAL INFORMATION (CONT.)

PERSISTENCE AND DEGRADABILITY

Conclusion / Summary : BOD value: 34000 mg/l
COD value: 1300000 mg/l

BIOACCUMULATIVE POTENTIAL

Product/ingredient name	LogPow	BCF	Potential
xylene	3.12	8.1 to 25.9	low
Butyl Cellosolve	0.81	-	low
Isopropyl alcohol	0.05	-	low

MOBILITY IN SOIL

Other adverse effects : No known significant effects or critical hazards.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

UNITED STATES - RCRA TOXIC HAZARDOUS WASTE "U" LIST

Ingredient	#CAS	Status	Reference number
Xylene	1330-20-7	Listed	U239





**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 14 - TRANSPORT INFORMATION

	DOT Classification	TDG Classification	IMDG	IATA
UN number	1307	1307	1307	1307
UN proper shipping name	XYLENES	XYLENES	XYLENES	XYLENES
Transport hazard class (es)	3	3	3	3
Packing group	III	III	III	III
Environmental hazards	No.	No.	Yes.	No.
Additional information	Reportable quantity 157.11 lbs / 71.33 kg [21.352 gal / 80.827 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.		The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.



Alliance Designer Products Inc.
 225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 15 - REGULATORY INFORMATION

CALIFORNIA PROP. 65

Not available.

Product/ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
--------------------------------	---------------	---------------------	----------------------------------	--

U.S. Federal regulations :

United States inventory (TSCA 8b) : All components are listed or exempted.
Clean Water Act (CWA) 311: xylene

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

SARA 302/304

COMPOSITION/INFORMATION ON INGREDIENTS

Not available.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

COMPOSITION/INFORMATION ON INGREDIENTS

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
xylene	≥52 - <75	Yes	No	No	Yes	Yes
Butyl Cellosolve	≥4 - <5	Yes	No	No	Yes	No
Isopropyl alcohol	≥3 - <4	Yes	No	No	Yes	No

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	xylene	1330-20-7	≥52 - <75
	Butyl Cellosolve	111-76-2	≥4 - <5
	Isopropyl alcohol	67-63-0	≥3 - <4
Supplier notification	xylene	1330-20-7	≥52 - <75
	Butyl Cellosolve	111-76-2	≥4 - <5
	Isopropyl alcohol	67-63-0	≥3 - <4



Alliance Designer Products Inc.
225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 15 - REGULATORY INFORMATION (CONT.)

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

STATE REGULATIONS

- Massachusetts** : The following components are listed: XYLENE; 2-BUTOXYETHANOL; ISOPROPYL ALCOHOL
- New York** : The following components are listed: Xylene (mixed)
- New Jersey** : The following components are listed: XYLENES; BENZENE, DIMETHYL-; 2-BUTOXY ETHANOL; BUTYL CELLOSOLVE; ISOPROPYL ALCOHOL; 2-PROPANOL
- Pennsylvania** : The following components are listed: BENZENE, DIMETHYL-; ETHANOL, 2-BUTOXY-; 2-PROPANOL

INTERNATIONAL LISTS

NATIONAL INVENTORY

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- Europe** : Not determined.


SECTION 16 -OTHER INFORMATION

HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARDS	0

The customer is responsible for determining the PPE code for this material.

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)



HISTORY

- Date of issue/Date of revision** : 27/01/2016.
- Date of previous issue version** : 17/07/2015.
- Version** : 1
- References** : - Hawley, G.G.; The Condensed Chemical Dictionary, 11th edition. New York N.Y.,Van Nostrand Reinold, 1987. - Manufacturer's Material Safety Data Sheet. - SAX, N.I.;Dangerous Properties of Industrial Materials. Toronto, Van Nostrand Reinold,



Alliance Designer Products Inc.
 225 Blvd. Bellerose West, Laval, Quebec, Canada H7L 6A1
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com



**GATOR CLEAN RPT REMOVER +
FOR CONCRETE PAVER, WETCAST & NATURAL STONES**

SDS Revision Date (dd/mm/yyyy): 27/01/2016

SECTION 16 -OTHER INFORMATION (CONT.)

6th edition, 1984. -List of pure teratogenic, mutagenic, and cancerogenic products.
Toxicological index of the Occupational Health and Safety Commission of Quebec.

NOTICE TO READER

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.